

SERVO LIST ALL ELECTRIC

JR SERVO AND EXTENSION REQUIREMENTS

CONTROLS	QTY	SERVO TYPE	QTY	LEAD EXT
Ailerons	2	JR 9411 HV	2	12"
			2	36"
Elevators	2	JR 3711 HV	2	48"
Rudder Swept or Std Fin	1	JR 9411 HV	1	48"
Nose Steering	1	JR 3711 HV		NA
Brake	1	Spektrum A6265	3	6"
			4	12"
Flaps	2	JR 8411 HV	1	
			2	36"
			2	3"
Gear doors	3	Spektrum A4030 Or JR 3711 HV	2	24"
Receiver	1	Spektrum AR 12120		
Battery	1	Duralite Mag-ion 3000 mah		

NOTE: IF EQUIPMENT OTHER THAN JR/ SPEKTRUM IS USED, CONSULT THAT MANUFACTURER FOR SIMILAR COMPONENTS.

***NOTE:** Reverse servos and Y-harnesses are not required when 2 servos are used with a JR Match Box or 12 channel receiver.

The JR Match Box can also be used on rudder and nose gear steering to avoid any need for reversed servos.

NOTE: As of 2015, most of these components are obsolete and not available. Consult your R/C manufacture for current and equivalent components. High voltage systems are now prevalent.